

U-WAVE Bluetooth

Wireless Data Collection System

Typical applications



U-WAVE-TMB (264-626)



U-WAVE-TCB (264-625)

Transmitter/Receiver



SPECIFICATIONS

	For Digimatic micrometers		For Digimatic calipers	
Model	U-WAVE-TMB (IP67 type)	U-WAVE-TMB (buzzer type)	U-WAVE-TCB (IP67 type)	U-WAVE-TCB (buzzer type)
Order No.	264-626	264-627	264-624	264-625
Protection level	IP67	N/A	IP67	N/A
Data reception indication	LED	LED, buzzer	LED	LED, buzzer
Power source	Lithium battery CR2032x1			
Battery life	Windows OS: Approx. 3 months, iOS/Android: Approx. 1 year			
Mass (g)	18			

Choose a connecting unit compatible with your gage.

Order No.	02AZF310	02AZF300
Protection level	IP67	N/A
Mass (g)	6	
Connectable transmission unit	U-WAVE-TMB/TCB (IP67)	U-WAVE-TCB (for standard type)

Note: Water-proof performance is ensured only when attached to measuring instruments of IP67 type.

Compatibility of measuring tool and unit

Digimatic gage	Assembled appearance (Front/Back)	Connecting unit	Transmission unit
Micrometer	Standard	02AZF310	264-627 U-WAVE-TMB (buzzer type)
	Quantu-Mike ¹	02AZF960	264-626 U-WAVE-TMB (IP67 type)
Caliper	Standard	02AZF300	264-625 U-WAVE-TCB (buzzer type)
	Coolant-proof type	02AZF310	264-624 U-WAVE-TCB (IP67 type)
Digimatic indicator	ID-C, ID-F Series (new type only) Type SF connector (for ID-C Series 12.7 mm type)	02AZF700	264-627 U-WAVE-TMB (buzzer type) 264-626 U-WAVE-TMB (IP67 type)
	Others	Connection cable Mounting bracket	02AZD880G U-WAVE-T (buzzer type) U-WAVE 02AZD730G U-WAVE-T (dust/water-proof type) U-WAVE

¹ 02AZF960 is applicable to new models (293-14X-40/293-18X-40).