


TESA ISOMASTER Standard Models with Analogue Indication

Slanted full millimetres on the barrel are set apart from the straight half millimetres to virtually eliminate reading errors. The knurled sleeve needs only be reversed to render the friction drive built into the thimble inactive.



						
00110101		0 ÷ 25	0,01	00120101	0 ÷ 1	0.0001
00110102		25 ÷ 50	0,01	00120102	1 ÷ 2	0.0001
00110103		50 ÷ 75	0,01	00120103	2 ÷ 3	0.0001
00110104		75 ÷ 100	0,01	00120104	3 ÷ 4	0.0001
00110105		100 ÷ 125	0,01			
00110106		125 ÷ 150	0,01			
00110107		150 ÷ 175	0,01			
00110108		175 ÷ 200	0,01			
00110109		200 ÷ 225	0,01			
00110110		225 ÷ 250	0,01			
00110111		250 ÷ 275	0,01			
00110112		275 ÷ 300	0,01			



Set of 4 TESA ISOMASTER

Same execution as above.

The models covering the application range 0 to 100 mm provide the quality that you need at competitive prices.

	
00110113	0 ÷ 100

ETALON Basic to 0,01 mm



	
00119046	0 ÷ 25
00119047	25 ÷ 50
00119048	50 ÷ 75
00119049	75 ÷ 100

Set of 4 ETALON Basic to 0,01 mm

	
00119050	0 ÷ 100



DIN 863 T1
NF E 11-095

Tungsten carbide
tipped

≤ 100 mm:
6,5 mm dia.
> 100 ≤ 300:
8 mm dia.

0,5 mm

Max. 10 N

Plastic case

Identification
number

Inspection report
with a declaration
of conformity



Plastic case



DIN 863 T1
NF E 11-095

0,01 mm

Tungsten carbide
tipped

6,5 mm dia.

0,5 mm

Max. 10 N

Plastic case

Identification
number

Inspection report
with a declaration
of conformity