


PLAIN RING GAGE

FEATURES:

- According to DIN 2250-C
- Made of hardened tool steel
- Hardness HRC60-63
- Special sizes are available upon request



unit:mm



Tolerance class of the hole according to DIN 2250-C is JS4 (DIN EN ISO 286):

- ±1.5µm (≤φ3mm)
- ±2.0µm (≤φ10mm)
- ±2.5µm (≤φ18mm)
- ±3.0µm (≤φ30mm)
- ±3.5µm (≤φ50mm)
- ±4.0µm (≤φ80mm)
- ±5.0µm (≤φ120mm)
- ±6.0µm (≤φ180mm)
- ±7.0µm (≤φ250mm)
- ±8.0µm (≤φ315mm)
- ±9.0µm (≤φ400mm)

Model No.	Size (φmm)
P9026-M3	3
P9026-M3.5	3.5
P9026-M4	4
P9026-M4.5	4.5
P9026-M5	5
P9026-M6	6
P9026-M7	7
P9026-M8	8
P9026-M9	9
P9026-M10	10
P9026-M11	11
P9026-M12	12
P9026-M13	13
P9026-M14	14
P9026-M15	15
P9026-M16	16
P9026-M17	17
P9026-M18	18
P9026-M19	19
P9026-M20	20
P9026-M21	21
P9026-M22	22
P9026-M23	23
P9026-M24	24
P9026-M25	25
P9026-M26	26
P9026-M27	27
P9026-M28	28
P9026-M29	29
P9026-M30	30
P9026-M31	31
P9026-M32	32
P9026-M33	33
P9026-M34	34
P9026-M35	35
P9026-M36	36
P9026-M37	37

Model No.	Size (φmm)
P9026-M38	38
P9026-M39	39
P9026-M40	40
P9026-M41	41
P9026-M42	42
P9026-M43	43
P9026-M44	44
P9026-M45	45
P9026-M46	46
P9026-M47	47
P9026-M48	48
P9026-M49	49
P9026-M50	50
P9026-M52	52
P9026-M54	54
P9026-M55	55
P9026-M56	56
P9026-M58	58
P9026-M60	60
P9026-M62	62
P9026-M64	64
P9026-M65	65
P9026-M66	66
P9026-M68	68
P9026-M70	70
P9026-M72	72
P9026-M74	74
P9026-M75	75
P9026-M76	76
P9026-M78	78
P9026-M80	80
P9026-M82	82
P9026-M84	84
P9026-M85	85
P9026-M86	86
P9026-M87	87
P9026-M88	88

Model No.	Size (φmm)
P9026-M90	90
P9026-M92	92
P9026-M95	95
P9026-M98	98
P9026-M100	100
P9026-M105	105
P9026-M110	110
P9026-M115	115
P9026-M120	120
P9026-M125	125
P9026-M130	130
P9026-M135	135
P9026-M140	140
P9026-M145	145
P9026-M150	150
P9026-M155	155
P9026-M160	160
P9026-M165	165
P9026-M170	170
P9026-M175	175
P9026-M180	180
P9026-M185	185
P9026-M190	190
P9026-M195	195
P9026-M200	200
P9026-M225	225
P9026-M250	250
P9026-M275	275
P9026-M300	300
P9026-M325	325
P9026-M350	350
P9026-M400	400